Harlequin Liberty HD

Harlequin Liberty HD is a development of our renowned Liberty sprung floor panel system, designed with enhanced durability in mind for more challenging environments. Harlequin Liberty HD is a birch plywood sprung floor panel system featuring shock dampening dual-density elastomer pads. The panels are coated with a black polymer resin, with a textured, high-grip pattern on the top surface which is high-wear, slip-resistant and weatherproof. The panels join using a rounded tongue and groove and are secured in place using our proprietary one turn of the key' latch and lock mechanism. Harlequin Liberty HD provides consistent shock dampening across the floor and offers the same feel and energy return to one or several dancers.

Performance surface: Harlequin Liberty HD can be used with a variety of Harlequin performance vinyls. Edge trims and ramps are available if required. For easy storage and transportation please see Harlequin's panel cart.

Installation: Harlequin Liberty HD is designed for both permanent or portable installation. The panels are laid in a 'brickwork fashion' onto the sub-floor so that cross joins do not coincide.




All Harlequin wooden sprung floors are 100% recyclable.



Harlequin sprung floor panel systems are extremely durable and are designed to be reused many times.

Specification Guide

| Specification Guide | |
|--|--|
| Permanent or Portable | Both |
| Panel Size | 2m x 1m & 1m x1m |
| Minimum Floor Thickness (before inclusion of chosen surface) | 37mm |
| Weight | 12.5kg/m² (Without surface) |
| Testing Standard | BS EN 14904:2006 |
| Shock Absorption | 67% |
| Vertical Deformation | 4.1mm |
| Area Deflection | 12.8% |
| Rolling Load | >1500 N |
| Testing Standard | BS EN 1991-1-1:2002 |
| Point Load | >3.60kN |
| Uniform Distributed Load | >10.00kN |
| Fire Rating | Bfls 1 to EN 13501 |
| Impact Generated Sound Level within room (Lw) | 104.20dB |
| Thermal Resistance - R Value | 1.52 m ² K/W |
| Thermal Insulation - U Value | 0.658 W/m ² K |
| Category of Use | A4 |
| VOC Emissions | <0.10 mg/m ³ |
| Mamanka | 10 years if installed by Harlequin |
| Warranty | 5 years if installed externally |
| Installation | Installed by Harlequin or the customer |
| Underfloor Heating | Suitable for use with underfloor heating |









Harlequin's 'latch and lock' system











underfloor heating

Harlequin

Liberty Accessories

The Harlequin Liberty sprung floor panel system has a range of accessories that complement the floor both practically and aesthetically. **Ramps, corner pieces and edge trims** can be used around the perimeter of the floor area to enable easy access on to the floor, eliminate trip hazards and hide the lock and latch mechanism. The accessories are made from a birch plywood coated with a textured black paint, they come in left and right-handed sections with corresponding latches and receivers.

Ramps & Corner Pieces: For use in situations where the sprung floor does not extend to the walls of the studio and for door thresholds. The ramps are DDA compliant.

Ramps:

Specification Guide

| Depth | 420mm |
|--------|---------|
| Length | 1m & 2m |
| Height | 37mm |

Corner Pieces:

Specification Guide

| Depth | 420mm |
|--------|-------|
| Length | 420mm |
| Height | 37mm |













Edge Trims: For use in situations where the sprung floor does not extend to the walls of the studio and for door thresholds.

Standard edge

| Depth | 65mm |
|--------|---------|
| Length | 1m & 2m |
| Height | 37mm |







Extra long (right/left)

| Depth | 65mm |
|--------|-------|
| Length | 2.06m |
| Height | 37mm |









Harlequin Liberty Panel Cart: The Harlequin Liberty panel cart enables the safe storage and handling of 22 Harlequin Liberty sprung floor panels. The cart is easy to manoeuvre with non-marking braked wheels.

- Stores up to 22 full size (2m x 1m) Harlequin Liberty sprung floor panels
- · Constructed from black scratch-resistant, powder-coated steel
- Fitted with four heavy-duty swivel castors with braeks and non-marking polyamide wheels
- Forklift pockets for side lifting

Specification Guide

| Width | 1270mm |
|---------------------|---------------------|
| Length | 2025mm |
| Height (For Panels) | 993mm |
| Total Height | 1211mm |
| Weight | Approximately 112kg |






Latch Key:

The panels join using a rounded tongue and groove and are secured in place using our proprietary 'one turn of the key' latch and lock mechanism.







If you would like further information or advice please contact us on +44(0) 1892 514 888 or enquiries@harlequinfloors.com

DANCE

The Company reserves the right to make any variation in design or construction of the material described. Harlequin ® is a registered trademark of British Harlequin plc. ® Harlequin Floors 07/2024



