Harlequin

Cascade

Harlequin Cascade is Harlequin's flagship professional vinyl performance floor, used by the world's leading dance companies and dance venues. As a hard-wearing homogeneous vinyl, it has a slip resistant smooth dance surface and is ideal for use in dance studios, theatres, concerts and as a high-quality base for lighting designers and photographers.

Installation: Harlequin Cascade is specified for permanent or temporary installation and is recommended for use in conjunction with a suitable Harlequin sprung floor. The joins are welded or taped to create a continuous performance surface.

Usage: Harlequin Cascade is a multi-purpose dance or stage floor, ideal for ballet, contemporary, modern and theatrical use. It is also the preferred vinyl dance floor for percussive dance (flamenco, Irish and tap).

Specification Guide

Material	Homogeneous vinyl
Permanent or Portable	Both
Roll Lengths	10m, 15m, 18m, 20m, 25m
Roll Width	2m
Thickness	2mm
Weight	2.6kg/m ²
Finish	Smooth
Fire Rating	Bfl-s1 (EN 13501-1)
Warranty	10 years if installed by Harlequin
	5 years if installed by the customer
Impact Sound Reduction	6dB, with Harlequin Activity sprung floor 22dB
Fixing Type	Adhesive or Tape
Seams	Welded or Taped
Light Reflectance	501-2, 406-8, 582-35, 470-11, 100-87
Gloss Level	Nominal 3
Lightfastness	≥6
Recycled Content	23-30%
VOC Emissions	≤0.1 mg/m³
Recyclability	100%
Underfloor Heating	Suitable for use with underfloor heating
Third Party Certification	Environmental Product Declaration A+ LEED, BREEAM, REACH Compliant

























The Australian Ballet









If you would like further information or advice please contact us on +44(0) 1892 514 888 or enquiries@harlequinfloors.com

The Company reserves the right to make any variation in design or construction of the material described. Harlequin ® is a registered trademark of British Harlequin plc. © Harlequin Floors 07/2023

